





GOVT. COLLEGE OF ENGINEERING AND RESEARCH, AWASARI

Awasari(Khurd) Tal: Ambegaon, Dist.Pune-412 405

Tel. No.02133-230582, E-Mail – gcoeara@gmail.com, Webesite: www.gcoeara.ac.in

No. GCOEARA/Store/2023/ 4798

Date

0 1 NOV 2023

To,

Prof.S.A. Thorat /Mr. A.D.Chavan for display on College Website

Subject: Quotation for supply of following material (for Instrumentation Dept.)

Please send your quotation for the following items on the terms and conditions listed below, mentioning our reference letter number, date and due date of quotation on your sealed envelop, on or before **21.11.2023** at 4.00 P.M. '

Sr. No.	ltem	Specification	Qty.	Rate	Total
1	IR Pair (Photodiode + LED)	5 IR - Led (Transmitter) + 5 Photo Diode (Receiver) Ideal for IR sensors Range: 700- 1050nm	10	200	
2	Tube Type Inductive Proximity Sensor	Output Type: NPN - NO, Red LED checks the state of the proximity sensor High repeated positioning accuracy, High switching frequency	5		
3	Capacitive Proximity Sensor	PNP - NO (Shielded) , Wire type and power : DC 3 - wire type 12-24VDC , Sensing side diameter : M18 , Sensing distance : 8mm	2		
4	Ultrasonic Sensor Modulę	HC - SR - 04 by Robokart	5		
5	Flex Sensor 2.2 "	length of 2.2 " , Connector is 0.1 " spaced	2		H
6	Stepper Motor	Speed 1.8 Degrees , Voltage 24 Volts , Horsepower 115 Watts , Item Dimensions LxWxH 40 x 42 x 42 Millimeters	2	*	
7	Temperature Sensor	LM61BIZ / LFT3 , Temperature Sensor Analog , Local -30 ° C ~ 100 ° C 10mV / ° C TO - 92-3	5		
8	Small DC Motor	Speed 6400 RPM , Voltage 24 Volts , 12 Volts	5		
9	Phototransistor	Max Collector to Emitter Breakdown Voltage : 25 V ;, Max Emitter to Base Breakdown Voltage : 12 V	5		

		Case: Clear Transparent Front Cover,			
10	Galvanometer	Desk Stand: Front Terminal			
		unbreakable ABS plastic Black Desk			
		Stand , Scale Length : 85mm (approx)	5		
		Accuracy : +/- 2 F.S.D			
		Packing: Thermocol Box			
	Analog Ammeter	Range = 10-0-10,30-0-30, 0-5 (2 Each)			
		Analog meter , 4mm plug leads			
11		• Accuracy : +/- 2 % , Unbreakable	5		
		Plastic , Range : 0-100mA , 0-5mA , 0			
	Analog Voltmeter	100microA (3 each)	5		
		Analog meter , 4mm plug leads			
12		• Accuracy : +/- 2 % , Unbreakable		l l	
		Plastic , Range : 0-100V , 0-10V , 0-5V ,			
	CRO Probes	DC (3 each)	10		
13		BNC to Crocodile Probe , 1.25 Meter			
		Length, Professional Grade	10		
14	Crocodile clips	Clips - Electronic Components	30		
15	Capacitive Proximity		2		
	switch		2		
16	Inductive Proximity		2		
		Total			

Terms & Conditions

1	Taxes - Inclusive /	if extra clearly mention	the percentage.
---	---------------------	--------------------------	-----------------

2 Delivery period -

3 Payment Terms -

4 Quotation Validity -

Mention clearly

- 5 Warranty -
- 6 Guaranty-
- 7 Delivery Charges Free / if extra mention clearly.
- 8 If you fail to supply the stores within the specified period, the order will be treated as cancelled without any information.
- 9 The material will be accepted subject at approval(after inspection of the material), If rejected it will be returned to you at your cost.
- 10 The material to be supplied should be strictly according to the specification only.
- 11 Octroi is not applicable since Institute is located in Gram Panychayat area.
- 12 Please attach copy of your shop **Registration Certificate** and **GST Registration Certificate** along with your quotation, without which your quotation will not be accepted.

(Dr. D. R. Pangavhane)

I/c Principal

Govt.College of Engineering & Research Awasari(Kh) Tal: Ambegaon, Dist.Pune